

Rain Harvesting Systems



Rainsaver MK4E Pressure Systems



Rainsaver MK4E Changeover Device.

Designed to operate with pumps up to 800kPa. 100L/m flow. 12V Low voltage Float. WaterMark approved for connection to all town water supplies. Aesthetically designed and requires no weather proofing. IP33. For self-controlled pumps up to 1.5hp, 1.1kW, 240V.



BIA-RAINSAVERMK4E

Model/Item Code	Description
BIA-RAINSAVERMK4E 805617	Designed to operate with pumps up to 800kPa. 100L/m flow. 12V Low voltage Float. IP33 For self controlled pumps up to 1.5hp, 1.3kW, 240V.
RS4E-INOX45S2MPCX 805332	Rainsaver MK4E & BIA-INOX45S2MPCX Stainless Steel 450W Electronic Self Priming Pump with Auto Restart, 395kPa, 58L/m
RS4E-INOX60S2MPCX 803793	Rainsaver MK4E & BIA-INOX60S2MPCX Stainless Steel 600W Electronic Self Priming Pump with Auto Restart, 430kPa, 62L/m
RS4E-INOX90S2MPCX 803794	Rainsaver MK4E & BIA-INOX90S2MPCX Stainless Steel 750W Electronic Self Priming Pump with Auto Restart, 500kPa, 79L/m
RS4E-BHMS-6MPCX 803151	Rainsaver MK4E & BIA-BHMS-6MPCX Stainless Steel 1300W Multistage Electronic Pump with Auto Restart, 590kPa, 145L/m
RS4E-B42ACMPCXBPH Builder's Pack 805666	Rainsaver MK4E, WHI-SK10AXHS2 adjustable electronic controller and BIA-B42ACMPCX. High Head Multistage Submersible 550W Clean Water Pump with built-in riser. Automatic Rainwater/Mains Water Changeover Device with auto restart pump controller are mounted in galvanised enclosure with easy access cover. 320 kPa, 94 L/m, 10m power cable
<p>Note: Taps shown above have been calculated at 10 litres per minute. Supplied with 10m power cable Includes 2 Year Rainsaver MK4E Infield Warranty</p>	



RS4E-INOX60S2MPCX



RS4E-BHM5-6MPCX



RS4E-B42ACMPCXBPH

