EnergysaverSpace Heaters



Relax. It's a Rinnai.



Comfortable, warm and efficient – a real breath of fresh air.

With a minimum energy efficiency rating of 4.8 Stars, our range of Energysaver® heaters outperform almost all other forms of heating. Sending out warm, clean air, they create zero emissions into the room, which is ideal for those susceptible to allergies or respiratory problems. This is achieved by the Energysaver's power flue system, which expels the combustion products outside leaving the air inside fresh and healthy. Also, all Energysaver heaters come with a humidifier tray. By adding water to the tray, the humidity in the room rises making it feel warmer and more comfortable.

Features and Benefits

- > High efficiency rating, reducing your heating costs
- > Superior indoor air quality with zero emissions into the room
- > Power flue design allows for flexible installation, with multiple options to suit your home
- > Full electronic thermostatic control that allows you to select a desired temperature which is then maintained by the heater
- > Inbuilt humidifier tray, easy way to humidify indoor air for greater comfort
- > Child lock prevents unwanted access
- > Available in both Natural Gas and LPG







559FT



561FT



1005FT

Additional Features

- > **Dual Digital Timers** allow for on and off programming for both mornings and evenings
- > **Pre-heat Mode** ensures your room reaches a comfortable temperature by the time programmed
- > **Economy Mode** allows the heater to modulate down after 1 hour when set temperature is reached. Reduces running costs with no noticeable change in temperature
- **Auto off** function operates when the minimum heat setting of the heater still has too much heat output to maintain the set temperature. If the auto-off feature is activated, the heater would turn off rather than heat the room above the set temperature.



......

. -----

Humidifier Tray



Control Panel


Flueing Options



1. Rear External Wall




2. Sideways External Wall*



3. Through Wall and Up



Min. 300mm vertical clearance from base of flue terminal



5. In wall Vertical

Backspacer Kit						
Model	Order Code					
Energysaver 309	ESBSKE					
Energysaver 559	ESBSKF					
Energysaver 561	ESBSKG					
Energysaver 1005	ESBSKH					

*Backspacer kit is required.

Orde	r Components	Order Code
1	Direct Flue Kit	ESDFK
2	Direct Flue Kit Co-Ax Pipe 900mm# Wall Plate Back Spacer Kit	ESDFK ESPIPE900 ESPLATE See below left
3 <i>A</i>	Direct Flue Kit Co-Ax Pipe 900mm# 90° Bend (2 x 45°) Condensate Trap Roof Cowl	ESDFK ESPIPE900 ESBEND ESCONDK ESROOFCOWL
3В	Direct Flue Kit Co-Ax Pipe 900mm# 2 x 90° Bends (4 x 45°) Condensate Trap Wall Terminal Kit	ESDFK ESPIPE900 2 X ESBEND ESCONDK ESWTKIT
4	Direct Flue Kit Wall Terminal Kit Co-Ax Pipe 900mm# 90° Bend (2 x 45°) Back Spacer Kit	ESDFK ESWTKIT ESPIPE900 ESBEND See below left
5A	In Wall Flue Kit Includes: Condensate Trap Roof Cowl 4 x Co-Ax Pipe 900mm	ESFKITIW
5B	Bends (2 x 45°) In Wall Flue Kit Includes: Condensate Trap Roof Cowl 4 x Co-Ax Pipe 900mm	ESBEND ESFKITIW

Specifications												
	Visual Dimensions* (mm)		Efficiency Star Rating AS4553	Colour	Gas Input - MJ/h		kW Out- put	'Heats up to' Capacity (m²)*				
	Height	Width	Depth			Low	High		Very Cold	Cold	Cool	Mild
Inbuilt												
309FT	695	465	257	4.8		6	13	2.9	27	32	42	49
559FDT ⁽²⁾	582	760	257	4.8		9	23	5.4	47	56	74	85
559FT	582	760	257	4.8	White	9	23	5.2	47	56	74	85
561FT	750	545	262	4.8		9	23	5.0	47	56	74	85
1005FT	670	930	330	4.8		15.5	37	8.6	75	89	119	138
1005FDT ⁽²⁾	670	930	330	4.8		15.5	37	8.6	75	89	119	138

^{*}Ask in-store or see online for your heating zone

Footures		,				,	
Features	Dual Timers	Delay Timer (FDT)	Pre-heat Feature	Economy Mode	Auto Off Mode	Override Button	Child Lock or Lock Button
309FT	√	√	√	✓	√	✓	√
559FDT ⁽²⁾		√			✓		√
559FT	✓	√	√	√	√	√	√
561FT	✓		✓	√	√	√	√
1005FT	√		√	√	√	√	√
1005FDT ⁽²⁾		✓			✓		√

Warranty	Heat Exchanger	Fan	All Other Parts	Free Labour	
Domestic Use	10 years pro rata ⁽¹⁾	2 years	1 year	1 year	
Commercial Use	1 year on all parts and labour				

Please note: For full definitions of Domestic and Commercial use, along with other conditions and exclusions, please refer to www.rinnai.com. au. Rinnai Australia Pty. Ltd. Reserves the right to make modifications and change specifications without notice. We will however endeavour to communicate any major changes well before implementation. (1) Full replacement cost in the 1st year, reducing 10% per year thereafter.(2) FDT models catered to commercial applications. 240V power is required on all models. A power cord and plug is fitted. If hardwiring is required, consult a licensed electrician. #Dimensions are subject to production tolerances and may vary slightly from those given. Rinnai Australia Pty Ltd reserves the right to make modification and change specifications without notice. #Refers to the visual appearance of the appliance external to the wall for inbuilt models.

Refer to our online heater selector to find the right heater to suit your needs.

	_			
Dea		D - 4-	. : 1	
1100	ıer	I JAT	alici	

