

MODEL	Indoor Units Combination Range	Refrigerant Pipe Diameter		Pipe Extension						Indoor Unit Combinations				
		Indoor Unit	Liquid Side (mm)	Gas Side (mm)	Maximum Pipe Length (1 room)	Maximum Pipe Length (Total)	Maximum Chargeless Length	Additional gas	Maximum Height	Capacity (kW class)	Type	Wall-Mounted	Mini Cassette	Ultra Slim Ducted
CU-ZZ52VBR INDOOR UNITS: Possible Combination Patterns Must be within capacity range 5.2kW *4 Dimensions (HxWxD): 619 x 624(L) x 299 mm Weight: 39 kg * At least two indoor units must be connected.	3,2 to 7,7 kW	Room A	ø 6,35	ø 9,52	20 m	30 m	20 m	15 g/m	10 m	2,0	• ¹⁵			
										2,5	•	•	•	
		Room B	ø 6,35	ø 9,52						3,5	•	•	•	•
										4,2	•			
										5,0	•	•	•	•
CU-3Z54VBR INDOOR UNITS: Possible Combination Patterns Must be within capacity range 5,4kW *4 Dimensions (HxWxD): 775 x 673(L) x 320 mm Weight: 71 kg * At least two indoor units must be connected.	4,5 to 9,5 kW	Room A	ø 6,35	ø 9,52	25 m	50 m	30 m	20 g/m	15 m	2,0	• ¹⁵			
										2,5	•	•	•	
		Room B	ø 6,35	ø 9,52						3,5	•	•	•	
										4,2	•			
		Room C	ø 6,35	ø 9,52						5,0	•	•	•	
CU-4Z71VBR INDOOR UNITS: Possible Combination Patterns Must be within capacity range 7,1kW *4 Dimensions (HxWxD): 795 x 673(L) x 320 mm Weight: 72 kg * At least two indoor units must be connected.	4,5 to 11,5 kW	Room A	ø 6,35	ø 9,52	25 m	60 m	30 m	20 g/m	15 m	2,0	• ¹⁵			
										2,5	•	•	•	
		Room B	ø 6,35	ø 9,52						3,5	•	•	•	
										4,2	•			
		Room C	ø 6,35	ø 9,52						5,0	•	•	•	
		Room D	ø 6,35	ø 9,52						6,0	•	•	•	

*2 To enable demand response management, an optional accessory needs to be installed (CZ-CAP2) *5 RZ Series only.

OUTDOOR UNIT

Up to 2 rooms

CU-ZZ52VBR

Up to 3 rooms

CU-3Z54VBR

Up to 4 rooms

CU-4Z71VBR

MODEL	Indoor Units Combination Range	Refrigerant Pipe Diameter		Pipe Extension						Indoor Unit Combinations				
		Indoor Unit	Liquid Side (mm)	Gas Side (mm)	Maximum Pipe Length (1 room)	Maximum Pipe Length (Total)	Maximum Chargeless Length	Additional gas	Maximum Height	Capacity (kW class)	Type	Wall-Mounted	Mini Cassette	Ultra Slim Ducted
CU-4Z80VBR INDOOR UNITS: Possible Combination Patterns Must be within capacity range 8,0kW *4 Dimensions (HxWxD): 999 x 740 x 340 mm Weight: 80 kg * At least two indoor units must be connected.	4,5 to 14,7 kW	Room A	ø 6,35	ø 9,52						2,0	• ¹⁵			
										2,5	•	•	•	
		Room B	ø 6,35	ø 9,52						3,5	•	•	•	
										4,2	•			
		Room C	ø 6,35	ø 9,52	25 m	70 m	45 m	20 g/m	15 m	5,0	•	•	•	
										6,0	•	•	•	
		Room D	ø 6,35	ø 9,52						7,1	•			
CU-5Z100VBR INDOOR UNITS: Possible Combination Patterns Must be within capacity range 10,0kW *4 Dimensions (HxWxD): 999 x 740 x 340 mm Weight: 81 kg * At least two indoor units must be connected.	4,5 to 18,3 kW	Room A	ø 6,35	ø 9,52						2,0	• ¹⁵			
										2,5	•	•	•	
		Room B	ø 6,35	ø 9,52						3,5	•	•	•	
										4,2	•			
		Room C	ø 6,35	ø 9,52	25 m	80 m	45 m	20 g/m	15 m	5,0	•	•	•	
										6,0	•	•	•	
		Room D	ø 6,35	ø 9,52						7,1	•			
		Room E	ø 6,35	ø 9,52										

*4 To enable demand response management, an optional accessory needs to be installed (CZ-CAP2) *5 RZ Series only.

ACCESSORIES

CZ-MA1PA
*1 CZ-MA1PA is to be used to reduce the connection size on the indoor unit from 1/2" to 3/8".

CZ-MA2PA
*2 CZ-MA2PA is to be used to increase the connection size on the outdoor unit from 3/8" to 1/2".

CZ-MA3PA
*3 CZ-MA3PA is to be used to reduce the connection size on the indoor unit from 3/8" to 1/2".

CZ-CAP2
*4 Demand response module CZ-CAP2.

OUTDOOR UNIT

Up to 4 rooms

CU-4Z80VBR

Up to 5 rooms

CU-5Z100VBR

